

Chest freezer ULT C75

110V/60H



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications

Technical

Gross volume	2,61 ft³
Net volume	2,5 ft³
Temp. range	-60°C to -86°C
Temp. probes	1/PT 1000
Compressor	Secop
Refrigerant	R-489A
Noise level	53 dB
Power consumption 24/h	4,05 kWh
Power consumption	1.478 kWh / year
Voltage	110 V
Frequency	60 Hz

Features

Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	1
Defrost	Manual
Battery Backup	48h
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø 0,47 in
Contact for remote alarm	YES

Material

Inner	Precoated white steel
Outer	Galvanized pre-coated steel

Dimensions

Height (with castors)	36,6 in
Width	21,8 in
Depth (incl. condenser)	22,8 in
Depth (incl. condenser & handle)	24,8 in
Net weight	99 lb

Internal dimensions

Height	18,3 in
Width	15,3 in
Depth	15,3 in
Insulation	3,1 in
Insulation type	PUR
Internal humidity	<5 %

ULT C75-UL



Product no.

N113051

Storage capacity

Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
2 in	8	5	40	N311210
3 in	5	5	25	N311310
4 in	4	5	20	N311410