

Chest freezer ULT C400

110V/60Hz



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Eco-friendly, HCFC-free Nature R refrigerant
- Efficient cyclopentane insulation
- ISO, ETL, ATEX Certifications

Specifications

Technical

Gross volume	13,52 ft³
Net volume	12,99 ft³
Temp. range	-60°C to -86°C
Temp. probes	1/PT 1000
Compressor	Secop
Refrigerant	R-489A
Noise level	55 dB
Power consumption 24/h	9 kWh
Power consumption	3.285 kWh / year
Voltage	110V
Frequency	60 Hz

Features

Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	4
Defrost	Manual
Battery Backup	48h
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø 0,47in
Contact for remote alarm	YES

Material

Inner	Precoated white steel
Outer	Galvanized pre-coated steel

Dimensions

Height (w. castors)	34,8 in
Width	61,5 in
Depth (incl. condenser)	24,8 in
Depth (incl. condenser & handle)	26,7 in
Net weight	176 lb

Internal dimensions

Height	25,0/15,2 in
Width	54,8/46,8 in
Depth	17,3 in
Insulation	3,15 in
Insulation type	PUR
Internal humidity	<5 %

ULT C400



Product no.

N113054

Storage capacity

Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
2 in	6	3	18	N311200
	11	24	264	N311220
			= 282	
3 in	4	3	12	N311300
	8	24	192	N311320
			= 204	
4 in	3	3	9	N311400
	5	24	120	N311420
			= 129	