

Chest freezer XLT C75

220-240V/50Hz



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 45001 Certified

Specifications	
Technical	
Gross volume	74 litres
Net Volume	71 litres
Temp. range	-40°C to -60°C
Temp. probes	1/PT 1000
Compressor	Embraco
Baskets (incl./optional)	1/2
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	4,0 kWh
Power consumption	1.460 kWh / year
Voltage	220-240V
Frequency	50 Hz
Features	
Audible and visual alarm	YES
Castors	NO
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø 12 mm
Connection for remote alarm	Optional
Material	
Inner	Precoated white steel
Outer	Galvanized pre-coated steel
Outer dimensions	
Height	870 mm
Width	555 mm
Depth (incl. condenser)	580 mm
Depth (incl. condenser & handle)	630 mm
Net weight	48 kg
Inner dimensions	
Height	466 mm
Width	387 mm
Depth	387 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	< 5 %

XLT C75





Product no. N112001

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	8	5	40	N311210
75 mm	5	5	25	N311310
100 mm	4	5	20	N311410