

Chest freezer XLT C400

110-120V/60Hz



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 45001 Certified

Specifications

Technical

Gross volume	13,52 ft ³
Net Volume	12,99 ft ³
Temp. range	-40°C to -60°C
Temp. probes	1/PT 1000
Compressor	Embraco
Baskets (incl./optional)	4/15
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	7,0 kWh
Power consumption	2.555 kWh / year
Voltage	110-120V
Frequency	60 Hz

Features

Audible and visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup	NO
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø 0,47in
Connection for remote alarm	Optional

Material

Inner	Precoated white steel
Outer	Galvanized pre-coated steel

Outer dimensions

Height (with castors)	34,8 in
Width	61,4 in
Depth (incl. condenser)	24,8 in
Depth (incl. condenser & handle)	26,7 in
Net weight	189 lbs

Inner dimensions

Height	31,1 in
Width	56,8 in
Depth	17,3 in
Insulation	3,1 in
Insulation type	PUR
Internal humidity	< 5 %

XLT C400



Product no.

N112054

Storage capacity

Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
2 in	6	3	18	N311200
	11	24	264	N311220
			= 282	
3 in	4	3	12	N311300
	8	24	192	N311320
			= 204	
4 in	3	3	9	N311400
	5	24	120	N311420
			= 129	