

Chest freezer ULT C75

110-120V/60Hz



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable

- Eco-friendly, HCFC-free Nature R refrigerant
- Efficient cyclopentane insulation
- ISO 9001, 14001 & 18001 OHSAS Certified

| Specifications | |
|--|-----------------------------|
| Technical | |
| Gross volume | 74 litres |
| Net volume | 71 litres |
| Temp. range | -60°C to -86°C |
| Temp. probes | 1/PT 1000 |
| Compressor | Secop |
| Refrigerant | R-489A |
| Noise level | 53 dB |
| Power consumption 24/h | 5,1 kWh |
| Power consumption | 1.862 kWh/year |
| Voltage | 110-120 V |
| Frequency | 60 Hz |
| Features | |
| Audible & visual alarm | YES |
| Castors | 4 |
| Integrated lock | YES |
| Inner lids | 1 |
| Defrost | Manual |
| Battery Backup | 48h |
| USB | NO |
| Data connection | NO |
| Digital controller with display | XR30CX |
| Data logging | NO |
| High/Low temperature alarm | YES |
| Porthole for external probe & CO2 backup | Ø 12 mm |
| Contact for remote alarm | YES |
| Material | |
| Inner | Precoated white steel |
| Outer | Galvanized pre-coated steel |
| Outer dimensions | |
| Height (with castors) | 930 mm |
| Width | 555 mm |
| Depth (incl. condenser) | 580 mm |
| Depth (incl. condenser & handle) | 630 mm |
| Net weight | 45 kg |
| Inner dimensions | |
| Height | 466 mm |
| Width | 390 mm |
| Depth | 390 mm |
| Insulation | 80 mm |
| Insulation type | PUR |
| Internal humidity | < 5 % |



| Storage capacity | | | | |
|------------------|--------------|--------------|--------------------|-------------|
| Box height | No. of boxes | No. of racks | Total no. of boxes | Product no. |
| 50 mm | 8 | 5 | 40 | N311210 |
| 75 mm | 5 | 5 | 25 | N311310 |
| 100 mm | 4 | 5 | 20 | N311410 |