

Chest freezer ULT C200



- Low cost of ownership
- Limited maintenance and On-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free Nature R refrigerant
- ISO 9001, 14001 & 18001 OHSAS Certified

Specifications	
Technical	
Gross volume	198 litres
Net volume	189 litres
Temp. range	-60°C to -86°C
Temp. probes	1/PT 1000
Compressor	Embraco
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	5,3 kWh
Power consumption	1.935 kWh / year
Voltage	230V
Frequency	50 Hz
Features	
Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	3
Defrost	Manual
Battery Backup	48h
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Prepared for external logging equipment	YES
Contact for remote alarm	YES
Material	
Inner	Precoated white steel
Outer	Galvanized pre-coated steel
Dimensions	
Height (with castors)	890 mm
Width	920 mm
Depth (incl. condenser)	630 mm
Depth (incl. condenser & handle)	680 mm
Net weight	65 kg
Internal dimensions	
Height	635/385 mm
Width	550/210 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

ULT C200



Product no. N113002

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	9	99	N311220
			= 117	
75 mm	4	3	12	N311300
	8	9	72	N311320
			= 84	
100 mm	3	3	9	N311400
	5	9	45	N311420
			= 54	