

Chest freezer MLT C75



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Efficient cyclopentane insulation
- Eco-friendly, HCFC-free R600a refrigerant
- ISO 9001, 14001 & 45001 Certified

Specifications	
Technical	
Gross volume	74 litres
Net Volume	71 litres
Temp. range	-10°C to -25°C
Temp. probes	1/PT 1000
Compressor	Secop
Baskets (incl./optional)	1/2
Refrigerant	R600a
Noise level	53 dB
Power consumption 24/h	0,52 kWh
Power consumption	190 kWh / year
Voltage	230V
Frequency	50 Hz
Features	
Probe & Power failure alarm	YES
Castors	YES, NOT MOUNTED
Integrated lock	YES
Inner lids	NO
Defrost	Manual
Battery Backup 48h	YES
USB	NO
Data connection	NO
Digital controller with display	XR30CX
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø12 mm
Prepared for external logging equipment	YES
Material	
Inner	Painted steel
Outer	Painted steel
Outer dimensions	
Height	870 mm
Width	555 mm
Depth (incl. condenser)	580 mm
Depth (incl. condenser & handle)	630 mm
Net weight	43 kg
Inner dimensions	
Height	466 mm
Width	387 mm
Depth	387 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

MLT C75	
Product no.	N114001

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	8	5	40	N311210
75 mm	5	5	25	N311310
100 mm	4	5	20	N311410